



Main

Range	Acti 9
Product or component type	Time delay auxiliary
Device short name	IATEt
[Uc] control circuit voltage	24...110 V DC impulse 24...240 V AC 50/60 Hz maintained

Complementary

Type of setting	Time delay configuration
Time delay range	2 s...10 min 2 s...10 h 6...60 s 1...10 s 6 s...1 h
Maximum output current	0.2 A holding 3 A inrush
Hold-in power consumption in VA	5 VA
Mounting mode	Fixed, on the left of TL or CT
Mounting support	DIN rail
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	60 mm
Colour	White
Overvoltage category	III
[Uimp] rated impulse withstand voltage	4 kV
[Ui] rated insulation voltage	440 V
Standards	EN/IEC 60669-2-2
Connections - terminals	Output connection: yellow clips Input connection: tunnel type terminals 2 cable(s) 2.5 mm ² flexible Input connection: tunnel type terminals 2 cable(s) 1.5 mm ² rigid
Wire stripping length	9 mm
Tightening torque	0.8 N.m
Range compatibility	Acti9 iCT Acti9 iTL
Market segment	Small commercial Residential
Compatibility code	IATEt

Environment

IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	40...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	85 g
Package 1 Height	2.3 cm
Package 1 width	8 cm
Package 1 Length	9 cm
Unit Type of Package 2	S03
Number of Units in Package 2	108
Package 2 Weight	9.897 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts & cables product

Contractual warranty

Warranty	18 months
----------	-----------