



Main

Range	ComPact
Product name	Compact INV
Product or component type	Switch disconnecter
Poles description	3P
Network type	DC AC
Network frequency	50/60 Hz
Handle colour	Red
[Ie] rated operational current	AC-21A: 200 A AC 50/60 Hz 220/240 V AC-21A: 200 A AC 50/60 Hz 380/415 V AC-21A: 200 A AC 50/60 Hz 440/480 V AC-21A: 200 A AC 50/60 Hz 480 V NEMA AC-21A: 200 A AC 50/60 Hz 500/525 V AC-21A: 200 A AC 50/60 Hz 660/690 V AC-22A: 200 A AC 50/60 Hz 220/240 V AC-22A: 200 A AC 50/60 Hz 380/415 V AC-22A: 200 A AC 50/60 Hz 440/480 V AC-22A: 200 A AC 50/60 Hz 480 V NEMA AC-22A: 200 A AC 50/60 Hz 500/525 V AC-22A: 200 A AC 50/60 Hz 660/690 V AC-23A: 200 A AC 50/60 Hz 220/240 V AC-23A: 200 A AC 50/60 Hz 380/415 V AC-23A: 200 A AC 50/60 Hz 440/480 V AC-23A: 200 A AC 50/60 Hz 480 V NEMA AC-23A: 200 A AC 50/60 Hz 500/525 V AC-23A: 200 A AC 50/60 Hz 660/690 V DC-21A: 200 A DC 125 V 2 poles in series DC-22A: 200 A DC 125 V 2 poles in series DC-23B: 200 A DC 125 V 2 poles in series
[Ui] rated insulation voltage	750 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	8 kV
[Ith] conventional free air thermal current	200 A at 60 °C
[Icm] rated short-circuit making capacity	30 kA switch-disconnector alone 690 V AC at 50/60 Hz 330 kA with upstream protection circuit breaker 690 V AC at 50/60 Hz
[Ue] rated operational voltage	250 V DC 690 V AC 50/60 Hz
Suitability for isolation	Yes
Contact position indicator	Yes
Visible break	Yes
Pollution degree	3

Complementary

Control type	Rotary handle
Mounting mode	Fixed
Mounting support	Plate Rail
Upside connection	Front
Downside connection	Front
Maximum power	AC-23: 110 kW at 440 V AC 50/60 Hz AC-23: 110 kW at 480 V AC 50/60 Hz (NEMA) AC-23: 132 kW at 500/525 V AC 50/60 Hz AC-23: 160 kW at 660/690 V AC 50/60 Hz AC-23: 55 kW at 220/240 V AC 50/60 Hz AC-23: 55 kW at 230 V AC 50/60 Hz (NEMA) AC-23: 90 kW at 380/415 V AC 50/60 Hz
Rated duty	Uninterrupted
[I _{cn}] rated short-time withstand current	1.8 kA during 30 s conforming to IEC 60947-3 2.2 kA during 20 s conforming to IEC 60947-3 4.9 kA during 3 s conforming to IEC 60947-3 8.5 kA during 1 s conforming to IEC 60947-3
Mechanical durability	15000 cycles
Electrical durability	AC-22A: 1500 cycles 440 V AC 50/60 Hz AC-22A: 1500 cycles 500 V AC 50/60 Hz AC-22A: 1500 cycles 690 V AC 50/60 Hz AC-23A: 1500 cycles 440 V AC 50/60 Hz AC-23A: 1500 cycles 500 V AC 50/60 Hz AC-23A: 1500 cycles 690 V AC 50/60 Hz DC-22A: 1500 cycles 125 V DC DC-23A: 1500 cycles 125 V DC
Connection pitch	45 mm
Height	136 mm
Width	140 mm
Depth	96 mm
Net weight	2 kg

Environment

Standards	IEC 60947-3 IEC 60947-1
Product certifications	CCC KEMA-KEUR
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	2.287 kg
Package 1 Height	13.7 cm
Package 1 width	16.2 cm
Package 1 Length	17 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Contractual warranty	
Warranty	18 months