

Product data sheet

Characteristics

34027

switch disconnector, Compact NS2000 NA,
fixed, front connected, manually operated,
2000 A, 3 poles



Main

Product name	ComPact NS
Device short name	Compact NS2000 NA
Product or component type	Switch disconnector
Device application	Distribution
Offer type	C5
Poles description	3P
Network type	AC
Performance level	NA
Suitability for isolation	Yes conforming to IEC 60947-3

Complementary

Network frequency	50/60 Hz
Control type	Toggle
Mounting mode	Fixed
Upside connection	Front
Downside connection	Front
[Ie] rated operational current	AC-23A: 2000 A AC 50/60 Hz 220/240 V AC-23A: 2000 A AC 50/60 Hz 380/415 V AC-23A: 2000 A AC 50/60 Hz 440/480 V AC-23A: 2000 A AC 50/60 Hz 500/525 V AC-23A: 2000 A AC 50/60 Hz 660/690 V
[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-3
[Ith] conventional free air thermal current	2000 A at 60 °C
[Icw] rated short-time withstand current	32 kA during 3 s conforming to IEC 60947-3
[Icm] rated short-circuit making capacity	135 kA 690 V AC at 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Mechanical durability	6000 cycles conforming to IEC 60947-3
Electrical durability	AC-23A: 1000 cycles 440 V AC 50/60 Hz conforming to IEC 60947-3
Connection pitch	115 mm
Height	350 mm
Width	420 mm
Depth	160 mm
Net weight	23 kg

Environment

Standards	IEC 60947-3
Product certifications	ASEFA ASTA
Pollution degree	3 conforming to IEC 60947-3
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Package 1 Weight	33.000 kg
Package 1 Height	43.000 cm
Package 1 width	60.000 cm
Package 1 Length	80.000 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------