



Main

Range	Acti9
Product name	Acti9 iID40
Product or component type	Residual current circuit breaker (RCCB)
Device short name	iID40
Poles description	3P + N
Neutral position	Left
[In] rated current	63 A
Network type	AC
Earth-leakage sensitivity	300 mA
Earth-leakage protection time delay	Instantaneous
Earth-leakage protection class	Type A-SI (Super Immunised)
Suitability for isolation	Yes conforming to EN/IEC 60947-2
Quality labels	CE

Complementary

Device location in system	Group incomer
Network frequency	50 Hz
[Ue] rated operational voltage	380...415 V AC 50 Hz
Residual current tripping technology	Voltage independent
Rated breaking and making capacity	I _{dm} 1500 A
Rated conditional short-circuit current	10000 A
[Ui] rated insulation voltage	500 V AC 50/60 Hz
[Uimp] rated impulse withstand voltage	6 kV
Contact position indicator	Yes
Control type	Toggle
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	8
Height	91 mm
Width	72 mm
Depth	74 mm
Net weight	364 g
Colour	White
Mechanical durability	20000 cycles
Electrical durability	15000 cycles
Connections - terminals	Tunnel type terminals bottom 1...35 mm ² rigid Tunnel type terminals bottom 1...25 mm ² flexible Tunnel type terminals top 1...16 mm ² rigid Tunnel type terminals top 1...10 mm ² flexible
Wire stripping length	14 mm for top or bottom connection
Tightening torque	3.5 N.m

Environment

Product certifications	CE
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Pollution degree	3
Electromagnetic compatibility	8/20 µs impulse withstand, 3000 A
Relative humidity	95 % at 55 °C

Packing Units

Package 1 Weight	0.364 kg
Package 1 Height	0.850 dm
Package 1 width	0.750 dm
Package 1 Length	1.000 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product