

# Product data sheet

## Characteristics

16017

cam ammeter switch CMA - 3L-N - 90° - 20 A -  
for Ø 22.3 mm



### Main

Range of product	PowerLogic
Product or component type	Selector switch
Device short name	CMA
Device application	Ammeter selector

### Complementary

[Ie] rated operational current	20 A
Mounting mode	Flush-mounted
Mounting support	Front face
Height	48 mm
Width	48 mm
Depth	69 mm
Mechanical durability	2000000 cycles
Electrical durability	100000 cycles

### Environment

Standards	IEC 60947-3
Ambient air temperature for operation	-25...50 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	119 g
Package 1 Height	5.5 cm
Package 1 width	5.5 cm
Package 1 Length	10.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	80
Package 2 Weight	10.095 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

### Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

---

Warranty	18 months
----------	-----------

---