Product data sheet Characteristics

LV847465

electric motor MCH, MasterPact MTZ1 drawout version, 100/130 V AC 50/60 Hz





| Main | |
|---------------------------|-----------------|
| Range | Masterpact |
| Device short name | MCH |
| Product or component type | Motor mechanism |
| Device application | Control |
| Range compatibility | Masterpact MTZ1 |

Complementary

| o in promortially | | |
|---------------------------------|------------------------------------|--|
| Control type | Standard | |
| Mounting mode | Drawout | |
| [Uc] control circuit voltage | 100130 V AC 50/60 Hz | |
| Threshold tripping voltage | 0.851.1 Un | |
| Maximum power consumption in VA | 180 VA | |
| Overcurrent protection | 23 x ln 0.1 s | |
| Maximum charging time | 3 s | |
| Maximum operating frequency | <= 3 cycles per minute | |
| Provided contact | Limit switch contact at 240 V 10 A | |
| | | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------|-------------------------------|
| REACh Regulation | REACh Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | ₽¥Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |