



Main

Range	TeSys
Product name	TeSys GF
Product or component type	Impulse relay
Device short name	GF16
Utilisation category	AC-1
Poles description	2P
Pole contact composition	1 NO + 1 NC
[Ie] rated operational current	16 A AC-1
[Ue] rated operational voltage	250 V AC 50/60 Hz
Permissible short-time rating	320 A 40 °C 1 s 48 A 40 °C 30 s 96 A 40 °C 10 s
Operating position	+/- 90° to vertical plane
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	24 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail

Complementary

[Ith] conventional free air thermal current	16 A (at 50 °C)
Average impedance	4 mOhm at 50 Hz - Ith 16 A
[Ui] rated insulation voltage	400 V conforming to IEC 60947-5-1 400 V conforming to VDE 0110
[Uimp] rated impulse withstand voltage	4 kV in enclosure
Connections - terminals	Control circuit: screw clamp terminals 1 cable(s) 1.5 mm ² solid without cable end Control circuit: screw clamp terminals 1 cable(s) 2.5 mm ² flexible with cable end Control circuit: screw clamp terminals 1 cable(s) 2.5 mm ² flexible without cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm ² flexible with cable end Control circuit: screw clamp terminals 2 cable(s) 1.5 mm ² solid without cable end Control circuit: screw clamp terminals 2 cable(s) 2.5 mm ² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 0.5...6 mm ² flexible with cable end Power circuit: screw clamp terminals 1 cable(s) 0.5...6 mm ² flexible without cable end Power circuit: screw clamp terminals 1 cable(s) 0.5...6 mm ² solid without cable end Power circuit: screw clamp terminals 2 cable(s) 0.5...4 mm ² flexible with cable end Power circuit: screw clamp terminals 2 cable(s) 0.5...4 mm ² flexible without cable end Power circuit: screw clamp terminals 2 cable(s) 0.5...4 mm ² solid without cable end
Tightening torque	Control circuit: 0.8 N.m - on screw clamp terminals Power circuit: 0.8 N.m - on screw clamp terminals
Operating time	70 ms closing 70 ms opening
Maximum operating rate	900 cyc/h
Control circuit voltage limits	0.85...1.1 U _c 50 °C 50/60 Hz

Impulse duration	>= 70 ms
Average consumption	19 VA AC 50 Hz at at Uc at 20 °C
Power dissipation per pole	1 W
Mechanical durability	1 Mcycles
Electrical durability	100000 Cycles AC-22 200000 cycles AC-21
9 mm pitches	2
Height	81 mm
Width	18 mm
Depth	64 mm
Net weight	0.11 kg
Quantity per set	Set of 12






Environment

Standards	IEC 60669-1 NF C 61-112 IEC 60669-2
IP degree of protection	IP40 conforming to VDE 0106 (in enclosure) IP20 conforming to VDE 0106
Protective treatment	TC
Ambient air temperature for operation	-20...50 °C
Ambient air temperature for storage	-40...80 °C
Operating altitude	<= 2000 m without derating
Mechanical robustness	Vibrations contactor open: 4 Gn, 5...300 Hz Vibrations contactor closed: 4 Gn, 5...300 Hz

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	120 g
Package 1 Height	8 cm
Package 1 width	9.4 cm
Package 1 Length	23 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Weight	1.44 kg
Package 2 Height	8 cm
Package 2 width	9.4 cm
Package 2 Length	23 cm
Unit Type of Package 3	S02
Number of Units in Package 3	48
Package 3 Weight	6.143 kg
Package 3 Height	15 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Halogen content performance	Halogen free plastic parts product

Contractual warranty

Warranty	18 months
----------	-----------