



Main

Range	Acti 9
Device short name	ICI
Product or component type	Impulse counter
Range compatibility	Prisma P door Prisma G door
Type of measurement	Impulse number
Display type	Electromechanical 7 digit(s)
Maximum value measured	9999999

Complementary

Full scale display	9999999
Impulse duration	50 ms
Time between 2 impulse	50 ms
Reset	Without
[Us] rated supply voltage	230 V AC at 50/60 Hz
Power consumption in VA	0.15 VA
Mounting mode	Fixed
Mounting support	DIN rail

Environment

9 mm pitches	4
Width	36 mm
Height	90 mm
Depth	67 mm

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	92 g
Package 1 Height	4 cm
Package 1 width	7.4 cm
Package 1 Length	9 cm
Unit Type of Package 2	S03
Number of Units in Package 2	72
Package 2 Weight	7.111 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------