

Product data sheet

Characteristics

15209

modular digital ammeter iAMP - 230V - 5..5000A



Main

Range	Acti 9
Device short name	iAMP
Product or component type	Ammeter
Range compatibility	Prisma P door Prisma G door
Network type	AC 50/60 Hz
Mounting support	DIN rail

Complementary

Type of measurement	Current
[Us] rated supply voltage	230 AC at 50/60 Hz
Power consumption in VA	0.3 VA
Power consumption in VA	0.3 VA
9 mm pitches	4
Width	36 mm
Height	87 mm
Depth	65 mm
Connections - terminals	Tunnel type terminal 2 cable(s) 2.5 mm ²

Environment

Standards	EN 50081-1 IEC 61010-1 EN 50082-1
Ambient air temperature for operation	-20...50 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	185 g
Package 1 Height	4 cm
Package 1 width	8 cm
Package 1 Length	9.2 cm
Unit Type of Package 2	S02
Number of Units in Package 2	36
Package 2 Weight	7.038 kg
Package 2 Height	15 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

REACH Regulation	<input checked="" type="checkbox"/> REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <input checked="" type="checkbox"/> EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<input checked="" type="checkbox"/> Yes
China RoHS Regulation	<input checked="" type="checkbox"/> China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------