



Main

Range	Acti 9
Device short name	IAMP
Product or component type	Ammeter
Range compatibility	Prisma P door Prisma G door
Technology type	Ferromagnetic
Scale type	Pseudo-linear scale over 90°
Mounting support	DIN rail

Complementary

Type of measurement	Current
Accuracy class	Class 1.5
Power consumption in VA	1.1 VA
Power consumption in VA	1.1 VA
Overload withstand	1.2 In, permanently 10 In, 5 s
9 mm pitches	8
Width	70 mm
Height	83 mm
Depth	66 mm
Temperature drift	+/- 0.03 %/°C
Connections - terminals	Tunnel type terminal rigid 1.5...6 mm ²

Environment

Standards	IEC 60051-1 IEC 61000-4 IEC 61010-1
Ambient air temperature for operation	-25...50 °C
Reference temperature	23 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	163 g
Package 1 Height	7.5 cm
Package 1 width	7.8 cm
Package 1 Length	9.2 cm
Unit Type of Package 2	S03
Number of Units in Package 2	45
Package 2 Weight	7.732 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------