



### Main

Range	Acti 9
Device short name	IVLT
Product or component type	Voltmeter
Range compatibility	Prisma P door Prisma G door
Scale	0-500 V
Technology type	Ferromagnetic
Scale type	Pseudo-linear scale over 90°
Mounting support	DIN rail

### Complementary

Type of measurement	Voltage
Accuracy class	Class 1.5
Power consumption in VA	3.5 VA
Power consumption in VA	3.5 VA
Overload withstand	1.2 Un, permanently 2 Un, 5 s
9 mm pitches	8
Width	70 mm
Height	83 mm
Depth	66 mm
Temperature drift	+/- 0.03 %/°C
Connections - terminals	Tunnel type terminal rigid 1.5...6 mm <sup>2</sup>

### Environment

Standards	IEC 61010-1 IEC 61000-4 IEC 60051-1
Ambient air temperature for operation	-25...50 °C
Reference temperature	23 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	163 g
Package 1 Height	7.8 cm
Package 1 width	7.5 cm
Package 1 Length	9.3 cm
Unit Type of Package 2	S03
Number of Units in Package 2	45
Package 2 Weight	7.781 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------