

# Product data sheet

## Characteristics

16075

voltmeter VLT PowerLogic - 96 x 96 -  
ferromagnetic - 0..500 V



### Main

Range	PowerLogic
Device short name	VLT
Product or component type	Voltmeter
Range compatibility	Prisma P door Prisma G door
Scale	0-500 V
Technology type	Ferromagnetic
Scale type	80 mm over 90°
Mounting support	Front face

### Complementary

Type of measurement	Voltage
Accuracy class	Class 1.5
Power consumption in VA	3 VA
Power consumption in VA	3 VA
Overload withstand	1.2 Un, permanently 2 Un, 5 s
Device mounting	Flush
Operating position	30°/vertical
Width	96 mm
Height	96 mm
Depth	75 mm
Temperature drift	+/- 0.003 %/°C

### Environment

Standards	IEC 61000-4 IEC 60051-1 IEC 61010-1
IP degree of protection	IP52
Ambient air temperature for operation	-25...50 °C
Reference temperature	23 °C

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	282 g
Package 1 Height	10.5 cm
Package 1 width	11 cm
Package 1 Length	11.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	12
Package 2 Weight	3.83 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

## Offer Sustainability

---

EU RoHS Directive

Compliant  EU RoHS Declaration

---

China RoHS Regulation

 China RoHS Declaration

---

WEEE

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---

## Contractual warranty

---

Warranty

18 months

---