Product data sheet Characteristics

A9MEM2100

modular single phase power meter iEM2100 - 230V - 63A



Main	
Range	Acti 9
Family	Acti 9 iEM2100
Device short name	IEM2100
Product or component type	Energy meter

Complementary

Complementary	
Poles description	1P + N
Type of measurement	Active energy
Device application	Sub billing
Accuracy class	Class 1 active energy conforming to IEC 62053-21
Input type	Direct input
Rated current	63 A
Rated voltage	230 V +/- 20 %
Network frequency	60 Hz 50 Hz
Frequency measurement range	4565 Hz
Technology type	Electronic
Display type	LCD display
Sampling rate	32 samples/cycle
Measurement current	063 A
Display digits	5
Maximum value measured	999.99 MWh
Tariff input	Tariff (1)
Communication port protocol	-
Communication port support	-
Local signalling	Green indicator light: power ON Yellow indicator light: metering and activity 1000 p/kWh
Digital inputs	0
Digital outputs	0
Maximum power consumption in VA	2.5 VA
Mounting mode	Clip-on
Mounting support	DIN rail
Connections - terminals	Power circuit: tunnel type terminals (bottom) 1 16 mm² cable(s)
Tightening torque	Power circuit: 1.5 N.m
Standards	IEC 61557-12 IEC 62053-21
Product certifications	CE

Environment

IP degree of protection	IP50 conforming to IEC 60529
IK degree of protection	IK05
Ambient air temperature for operation	-2070 °C -2055 °C
Ambient air temperature for storage	-4070 °C
Relative humidity	095 % at 55 °C
Colour	White
9 mm pitches	4
Width	36 mm
Height	81 mm
Depth	65 mm
Net weight	0.135 kg

Packing Units

Package 1 Weight	0.172 kg	
Package 1 Height	0.780 dm	
Package 1 width	0.950 dm	
Package 1 Length	0.450 dm	

Offer Sustainability

EU RoHS Directive	Compliant EEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration