



Main

Range of product	Acti 9
Product name	Acti 9 iPRF1
Product or component type	Surge arrester
Device short name	IPRF1 12.5r
Device application	Distribution
Poles description	3P
Remote signalling	With
Signal contacts composition	1 SD (1 C/O)
Surge arrester type	Electrical distribution network
Earthing system	IT 230 TN-C

Complementary

Surge arrester class type	Type 1 + 2
Surge arrester technology	MOV
[Ue] rated operational voltage	230/400 V AC (+/- 10 %) at 50/60 Hz
[In] nominal discharge current	Common mode: 25 kA (L/PE)
[Imax] maximum discharge current	50 kA
[Iimp] impulse current	Common mode: 12.5 kA L/PE 6.25 A.s
[Uc] maximum continuous operating voltage	Common mode: 350 V L/PE
Maximum [Up] voltage protection level	Common mode <1.5 kV type 1 L/PE
Disconnecter device type	Associated circuit breaker NG125N 80 A curve C - Icu 15 kA Associated circuit breaker NG125N 80 A curve C - Icu 25 kA Associated circuit breaker NG125H 80 A curve C - Icu 36 kA Associated circuit breaker NG125L 80 A curve C - Icu 50 kA Associated fuse gG 160 A standard Associated circuit breaker C120N 80 A curve C - Icu 10 kA
[Iscrr] short-circuit current rating : double fault	50 kA
Signalling circuit voltage	1.5 A/250 V AC 50/60 Hz
Mounting mode	Clip-on
Mounting support	DIN rail
9 mm pitches	8
Height	81.4 mm
Width	72 mm
Depth	71 mm
Net weight	0.59 kg
Colour	White (RAL 9003)
Material	PA6
Response time	<= 25 ns
Connections - terminals	Tunnel type terminal10...25 mm ² flexible Tunnel type terminal10...35 mm ² rigid
Tightening torque	2.5 N.m

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Standards	EN 61643-11:2012 IEC 61643-11:2011
Product certifications	CE
IP degree of protection	IP40 on front face: conforming to IEC 60529 IP20 built-in: conforming to IEC 60529
IK degree of protection	IK05 conforming to IEC 62262
Relative humidity	5...95 %
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...80 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	594 g
Package 1 Height	8 cm
Package 1 width	8.5 cm
Package 1 Length	9.5 cm
Unit Type of Package 2	S03
Number of Units in Package 2	24
Package 2 Weight	14.664 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------