




Main

Device short name	MN delay unit
Product or component type	Time delay relay
Device application	Control
Range compatibility	ComPact NSX PowerPact Multistandard ComPact NSX DC EasyPact CVS ComPact NSXm
Voltage release type	Undervoltage release
[Uc] control circuit voltage	48 V AC 50/60 Hz

Complementary

Impulse duration	200 ms
Time delay range	200 ms
Threshold tripping voltage	0.35...0.7 x Un opening 0.85 x Un closing
Supply holding power	4.5 VA
Supply inrush power	200 VA
Mounting mode	External mounting
Response time	<= 200 ms

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	133 g
Package 1 Height	7.8 cm
Package 1 width	8.6 cm
Package 1 Length	9 cm
Unit Type of Package 2	S03
Number of Units in Package 2	15
Package 2 Weight	2.482 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------