



Main

Device short name	MN
Product or component type	Voltage release
Device application	Control
Range compatibility	MasterPact NT Masterpact NW ComPact NS630b...1600 ComPact NS1600b...3200
Voltage release type	Undervoltage release
[Uc] control circuit voltage	48 V AC 50/60 Hz 48...60 V DC

Complementary

Threshold tripping voltage	0.35...0.7 x Un opening 0.85 x Un closing
Supply holding power	4.5 W
Mounting mode	Fixed
Response time	40 ms (Masterpact NT) 90 ms (Masterpact NW) 90 ms (Compact NS630b...1600) 90 ms (Compact NS1600b...3200)
Accessory / separate part category	Spare parts for Masterpact NT Spare parts for Masterpact NW Spare parts for Compact NS1600b...3200 Spare parts for Compact NS630b...1600

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	151 g
Package 1 Height	3.4 cm
Package 1 width	6.2 cm
Package 1 Length	8.3 cm
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Weight	1.554 kg
Package 2 Height	13 cm
Package 2 width	9 cm
Package 2 Length	19 cm
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Weight	9.747 kg
Package 3 Height	30 cm
Package 3 width	30 cm
Package 3 Length	40 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------