



### Main

|                           |                               |
|---------------------------|-------------------------------|
| Range of product          | Acti 9                        |
| Product name              | Acti 9 STD                    |
| Product or component type | Remote control dimmer         |
| Device short name         | STD                           |
| Function available        | Automatic load type detection |

### Complementary

|                                |  |
|--------------------------------|--|
| Device application             | Building   |
| Load type                      | Halogen lamp: $\leq 400$ W<br>Incandescent lamp: $\leq 400$ W<br>Fluocompact lamp, dimmable: $\leq 80$ W<br>LED lamp, dimmable: $\leq 60$ W<br>Low voltage halogen lamp with electronic transformer: $\leq 300$ W<br>Low voltage halogen lamp with ferromagnetic transformer: $\leq 400$ W |
| Control type                   | Local control: push-button<br>Remote control: push-button  |
| Power consumption in VA        | 0.8 VA   |
| Thermal losses                 | 3 W  |
| [Ue] rated operational voltage | 230 V AC - 15...10 % at 50 Hz  |
| Input voltage                  | 8...230 V AC/DC  |
| Protection type                | Electronic overload protection<br>Electronic over temperature protection   |
| Mounting support               | DIN rail   |
| 9 mm pitches                   | 2  |
| Connected auxiliaries          | Maximum 10 auxiliary push-buttons without light indication, distance : $< 100$ m   |
| Dimmer type                    | Dimmer with memory   |
| Height                         | 85 mm  |
| Width                          | 18 mm  |
| Depth                          | 60 mm  |
| Net weight                     | 65 g   |

### Environment

|                                       |   |
|---------------------------------------|---|
| IP degree of protection               | IP20  |
| Standards                             | EN 60669-2-1<br>EN 60669-1  |
| Directives                            | 2006/95/EC - low voltage directive<br>2004/108/EC - electromagnetic compatibility |
| Ambient air temperature for operation | -30...50 °C   |
| Ambient air temperature for storage   | -20...70 °C   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Weight             | 108 g    |
| Package 1 Height             | 3.3 cm   |
| Package 1 width              | 8.3 cm   |
| Package 1 Length             | 10.5 cm  |
| Unit Type of Package 2       | S03      |
| Number of Units in Package 2 | 86       |
| Package 2 Weight             | 9.906 kg |
| Package 2 Height             | 30 cm    |
| Package 2 width              | 30 cm    |
| Package 2 Length             | 40 cm    |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | <a href="#">End Of Life Information</a>       |