



Main

Range of product	Acti 9
Product name	Acti 9 MIN
Device short name	MINs
Product or component type	Silent electronic timer
Product compatibility	Mechanical compatibility with electrical comb busbars
Colour tint	White (RAL 9003)

Complementary

Device application	Building
Load type	230 V AC halogen lamp 2300 W 230 V AC incandescent lamp 2300 W Fluorescent lamp 9 x electronic ballast 7 W Dual mounted fluorescent tubeconventional ballast 2300 VA Fluorescent tubeelectronic ballast 300 VA Non-corrected fluorescent tubeconventional ballast 2300 VA Serial-corrected fluorescent tubeconventional ballast 2300 VA Fluorescent lamp 7 x electronic ballast 11 W Fluorescent lamp 7 x electronic ballast 15 W Fluorescent lamp 7 x electronic ballast 20 W Fluorescent lamp 7 x electronic ballast 23 W Fluocompact lampconventional ballast 1500 VA Parallel-corrected fluorescent tubeconventional ballast 400 VA
Maximum power consumption in VA	6 VA
Maximum switching current	16 A - 230 V AC pf = 1
[Ue] rated operational voltage	230 V AC +10 % -15 % at 50/60 Hz
Time delay	Adjustable from 0.5 to 20 minutes
Mounting support	DIN rail
9 mm pitches	2
Connections - terminals	Screw terminals - ≤ 6 mm ²
Electrical insulation class	Class II
Width	18 mm
Height	89 mm
Depth	66 mm
Net weight	75 g

Environment

Ambient air temperature for operation	-10...50 °C
IP degree of protection	IP20 B

Packing Units

Package 1 Weight	0.094 kg
Package 1 Height	0.700 dm
Package 1 width	0.700 dm
Package 1 Length	1.000 dm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------