




Main

Product or component type	Communication card
Range compatibility	Altivar 61 Altivar 71Q Altivar 71 Altivar 61Q
Communication port protocol	Profibus DP V1
Connector type	9-way female SUB-D connector
Transmission rate	19.2 kbps 500 kbps 3 Mbps 93.75 kbps 6 Mbps 187.5 kbps 1.5 Mbps 12 Mbps 9600 bps

Complementary

Number of addresses	1...126
Communication service	CiA 402 profile I/O profile I/O data Communication monitoring can be inhibited, adjustable PPO type 5 PPO type 3 PPO type 4 PPO type 8
Display type	1 LED for DX (data exchange) 1 LED for ST (status) Graphic display terminal for control word received Graphic display terminal for I/O data Graphic display terminal for reference received
Net weight	0.3 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	296 g
Package 1 Height	7.5 cm
Package 1 width	16.5 cm
Package 1 Length	23.3 cm
Unit Type of Package 2	S03
Number of Units in Package 2	7
Package 2 Weight	2.522 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm
Unit Type of Package 3	P06
Number of Units in Package 3	56
Package 3 Weight	30.78 kg
Package 3 Height	80 cm

Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------