

VW3A4510

DC choke - 0.52 mH - 85 A - for variable speed drive



Main

Product or component type	DC choke
Range compatibility	Altivar 61 Altivar 71
Device application	Reduction of current harmonics
Value of inductance	0.52 mH
[In] rated current	84.5 A
Thermal losses	98.3 W
Product compatibility	ATV71WD37N4 ATV71WD30N4 ATV61HD15M3X ATV71WD22N4 ATV71HD22N4 ATV71HD11M3X ATV71HD30N4 ATV61HD30N4 ATV61HD11M3X ATV71HD15M3X ATV71HD37N4 ATV61HD22N4 ATV61HD37N4
Electrical connection	Earth circuit terminal, connection capacity: 10 mm ² (AWG 6) Power supply terminal, connection capacity: 35 mm ² (AWG 0)

Complementary

Network number of phases	3 phases
Supply frequency	50...60 Hz
Maximum voltage drop at rated load	6 %
Max current	1.65 x nominal current (duration = 60 s)
Tightening torque	1.2...1.4 N.m for earth circuit 2.5...3 N.m for power supply
Height	171 mm
Width	126 mm
Depth	170 mm
Net weight	6.4 kg

Environment

IP degree of protection	IP20
Relative humidity	0...95 %
Ambient air temperature for operation	50...60 °C (with current derating 2.2 % per °C) -10...50 °C (without current derating)
Ambient air temperature for storage	-40...65 °C
Operating altitude	<= 1000 m without current derating 1000...3000 m with current derating 1 % per 100 m

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	7.62 kg
Package 1 Height	20 cm
Package 1 width	22 cm
Package 1 Length	32 cm
Unit Type of Package 2	CAR
Number of Units in Package 2	1
Package 2 Weight	8.048 kg
Package 2 Height	32 cm
Package 2 width	20 cm
Package 2 Length	22 cm
Unit Type of Package 3	P06
Number of Units in Package 3	10
Package 3 Weight	93.48 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------