



Main

Product or component type	Communication card
Range compatibility	Altivar 312 Solar Altivar 312
Communication port protocol	Profibus DP
Electrical connection	1 connector RJ45, Modbus 1 removable screw terminal block for inputs/outputs Screw terminal block, Profibus DP
Transmission rate	9600 bps, 19.2, 93.75, 187.5, 500 kbps, 1.5, 3, 6 or 12 Mbps
Number of addresses	1...127

Complementary

Input/output number	AI2 and AI3: 2 analog input LI1...LI3: 3 logic input R2: 1 relay output
Communication service	Periodic variables output : 4 PKW and 2 PZD CiA 402 profile Messaging via PKW periodic variables Periodic variables input : 4 PKW and 2 PZD
Display type	1 LED 1 LED for ST (status)
Net weight	0.2 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	199 g
Package 1 Height	7.5 cm
Package 1 width	17.5 cm
Package 1 Length	23.5 cm
Unit Type of Package 2	S04
Number of Units in Package 2	16
Package 2 Weight	4.142 kg
Package 2 Height	30 cm
Package 2 width	40 cm
Package 2 Length	60 cm
Unit Type of Package 3	P06
Number of Units in Package 3	64
Package 3 Weight	26.244 kg
Package 3 Height	80 cm
Package 3 width	80 cm
Package 3 Length	60 cm

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------