



Main

Range of product	Altivar
Product or component type	EMC input filter
Range compatibility	Altivar 61 Altivar 71
Product compatibility	ATV61HU22M3 ATV61HU30M3 ATV61HU30N4 ATV61HU40M3 ATV61HU40N4 ATV71HU22M3 ATV71HU30M3 ATV71HU30N4 ATV71HU40M3 ATV71HU40N4 ATV71PU30N4Z ATV71PU40N4Z ATV71WU30N4 ATV71WU40N4
Product specific application	Radio interference input filter
[In] rated current	26 A
Thermal losses	18 W for 200...240 V AC ATV61/ATV71 variable speed drives 6 W for 380...480 V AC ATV61/ATV71 variable speed drives
Network number of phases	Three phase

Complementary

Electrical connection	Terminal 6 mm ² AWG 8
Tightening torque	1.5 N.m
Maximum earth leakage current	8 mA at 400 V 50 Hz 4.4 mA at 400 V 50 Hz
Power supply voltage	200...240 V 380...500 V
Tolerance	10 %
Net weight	4 kg

Environment

IP degree of protection	IP20 IP41 (upper part)
Relative humidity	0...93 % conforming to IEC 68-2-3
Ambient air temperature for operation	-10...50 °C
Ambient air temperature for storage	-40...65 °C
Operating altitude	1000...3000 m with current derating 1 % per 100 m
Vibration resistance	1 gn (f= 13...150 Hz) conforming to IEC 60068-2-6 1.5 mm peak to peak (f= 3...13 Hz) conforming to IEC 60068-2-6
Shock resistance	15 gn for 11 ms conforming to EN/IEC 60068-2-27
Standards	EN 133200 EN/IEC 61800-3

Packing Units

Package 1 Weight	4.965 kg
Package 1 Height	1.300 dm
Package 1 width	5.900 dm
Package 1 Length	2.550 dm


Offer Sustainability

REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------

Dimensions



Dimensions in mm


a	b	c	G	H	Ø
155	324	50	130	309	4.5

Dimensions in in.

a	b	c	G	H	Ø
6.10	12.75	1.97	5.12	12.16	0.18

Mounting Recommendations

Mounting the Filter Under the Drive



Mounting the Filter Next to the Drive

