



**Main**

Range of product	BC Imprego
Product or component type	Dry type transformer
Network type	AC
Type of installation	Indoor

**Complementary**

Type of cooling	AN (air natural)
Rated power	6.3 kVA
Network frequency	50/60 Hz
Thermal class	Class F
Phase description	1 phase
Primary voltage	230 V
Isolation level	1.1 KV primary 1.1 KV secondary
[Ui] rated insulation voltage	Primary circuit: 1.1 KV AC Secondary circuit: 1.1 KV AC
Secondary voltage	With middle point: 230 V
Vector group	Li00
Temperature rise	100 K (winding)
Impedance voltage	2.7 %
No-load losses	60 W
Load losses	170 W
Operating altitude	< 1000 m
Winding material	Aluminium
Temperature class	H
Insulation material	Impregnated (LV)
Mounting mode	Fixed
IP degree of protection	IP00
Net weight	55 kg
Height	510 mm
Width	262 mm
Length	405 mm
Sound power level	65 dB at 1 m
Protection device	Vigitherm

## Environment

Ambient air temperature for operation	-25...40 °C for C4
Ambient air temperature for storage	-25...50 °C C2
Environmental certification	0...93 % (E2)
Fire certificate	F1
Atmospheric-corrosivity category	C3
Standards	EN/IEC 61558-2-15

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	62 kg
Package 1 Height	59 cm
Package 1 width	60 cm
Package 1 Length	80 cm
Unit Type of Package 2	P06
Number of Units in Package 2	1
Package 2 Weight	70.5 kg
Package 2 Height	50 cm
Package 2 width	80 cm
Package 2 Length	60 cm

## Offer Sustainability

EU RoHS Directive	Under investigation
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------