



Main

Product or component type	Spreader
Accessory / separate part category	Trunking accessory
Range compatibility	Enclosure enclosure
Cabling installation system	Housing wall trunking
Number of 18 mm modules per row	18
Product destination	For floor For ceiling
Standards	NF EN 50085-2-1 NFC 15-100

Complementary

Material	Plastic satin
Fire resistance	750 °C conforming to EN/IEC 60695-2-11
Quantity per set	Set of 1
IP degree of protection	IP40 conforming to EN/IEC 60529
IK degree of protection	IK08 conforming to IEC 62262 IK08 conforming to EN 50102
Depth	160 mm
Height	220 mm
Width	476 mm
Colour tint	White (RAL 9003)

Environment

Ambient air temperature for operation	-15...60 °C
---------------------------------------	-------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	788 g
Package 1 Height	16 cm
Package 1 width	23 cm
Package 1 Length	48.5 cm
Unit Type of Package 2	P12
Number of Units in Package 2	24
Package 2 Weight	18.912 kg
Package 2 Height	81 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile