

Main

Range of product	SPD910
Product or component type	Pressure transmitter sensor
Type of measurement	Differential pressure
Device application	Pump and compressor monitoring
Burst pressure	20" W.C. (5 kPa)
Controlled fluid	Air
Fitting size	6.2 mm (0.24")
Fitting type	Male
IP degree of protection	IP54
Location	Plant room
Mounting support	Pipe
Net weight	0.93 kg
Pressure measurement range	0.08...1.2" W.C. (20...300 Pa)
Ambient air temperature for operation	-30...85 °C
Ambient air temperature for storage	-40...85 °C
Standards	ETL CE 73/23/EWG DIN 1854 90/396/EWG CE 0085 A P0918
[Us] rated supply voltage	250 V AC
Targeted region	Middle East and Africa. Asia Pacific.

Complementary

Cable gland type	Pg 11
Measurement range	500...2000 Pa
Mounting mode	Pipe
Material	PC 10 % GF: case PC: cover Silicon: diaphragm
Rated voltage	250 V AC inductive 0.8 A 250 V AC resistive 5 A 30 V DC inductive 0.7 A 30 V DC resistive 4 A
Output type	Switch output 3-wire
Electrical connection	Screw terminal
Display type	Dial

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.6 cm
Package 1 Width	20.2 cm
Package 1 Length	7.2 cm
Package 1 Weight	274.0 g

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Contractual warranty

Warranty	24 months
----------	-----------