



### Main

|                                       |   |
|---------------------------------------|---|
| Range of product                      | SPP920  |
| Product or component type             | Pressure transmitter sensor                                   |
| Sensor model                          | SPP920-060  |
| Type of measurement                   | Differential pressure   |
| Device application                    | Pump and compressor monitoring<br>Energy and water management |
| Burst pressure                        | 145 psig (10 bar)   |
| Product certifications                | CE  |
| Controlled fluid                      | Water   |
| Fitting size                          | G 1/8"  |
| Fitting type                          | Female  |
| IP degree of protection               | IP65  |
| Location                              | Plant room  |
| Mounting support                      | Pipe  |
| Depth                                 | 65 mm   |
| Height                                | 94 mm   |
| Net weight                            | 1000 g  |
| Width                                 | 65 mm   |
| Pressure measurement range            | 0.22...0.9 psi (15...60 mbar)                                 |
| Ambient air temperature for operation | -10...80 °C   |
| Wiring technique                      | 3-wire  |
| Calibration certificate               | None  |
| Load type                             | Resistive : 1 A at 250 V AC<br>Inductive : 0.5 A at 250 V AC  |
| [Us] rated supply voltage             | 250 V AC  |
| Targeted region                       | Europe<br>Asia Pacific.                                       |

### Complementary

|               |                      |
|---------------|----------------------|
| Mounting mode | Pipe                 |
| Output type   | Switch output 3-wire |
| Material      | Brass: enclosure     |
| Display type  | Without display      |

### Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 8.5 cm   |
| Package 1 Width              | 12.4 cm  |
| Package 1 Length             | 11.9 cm  |
| Package 1 Weight             | 1.844 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |   |
|----------------------------|---|
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |