



### Main

|                                       |                                                               |
|---------------------------------------|---------------------------------------------------------------|
| Range of product                      | SPP930                                                        |
| Product or component type             | Pressure transmitter sensor                                   |
| Sensor model                          | SPP930-6000                                                   |
| Type of measurement                   | Differential pressure                                         |
| Device application                    | Pump and compressor monitoring<br>Energy and water management |
| Burst pressure                        | 99 psig (6.8 bar)                                             |
| Product certifications                | CE                                                            |
| Controlled fluid                      | Water                                                         |
| Fitting size                          | G 1/4"                                                        |
| Fitting type                          | Male                                                          |
| IP degree of protection               | IP54                                                          |
| Location                              | Plant room                                                    |
| Mounting support                      | Pipe                                                          |
| Depth                                 | 59 mm                                                         |
| Height                                | 94 mm                                                         |
| Net weight                            | 200 g                                                         |
| Width                                 | 65 mm                                                         |
| Pressure measurement range            | 15...87 psi (1...6 bar)                                       |
| Ambient air temperature for operation | -10...80 °C                                                   |
| Wiring technique                      | 3-wire                                                        |
| Calibration certificate               | None                                                          |
| Load type                             | Resistive : 6 A at 250 V AC<br>Inductive : 3 A at 250 V AC    |
| [Us] rated supply voltage             | 250 V AC                                                      |
| Targeted region                       | Europe<br>Asia Pacific.                                       |

### Complementary

|               |                      |
|---------------|----------------------|
| Mounting mode | Pipe                 |
| Output type   | Switch output 3-wire |
| Material      | Brass: enclosure     |
| Display type  | Without display      |

### Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 9.0 cm  |
| Package 1 Width              | 8.6 cm  |
| Package 1 Length             | 8.7 cm  |
| Package 1 Weight             | 298.0 g |

## Offer Sustainability

|                            |                                               |
|----------------------------|-----------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| REACH free of SVHC         | Yes                                           |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes                                           |
| Mercury free               | Yes                                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |