

### Main

Range	HS2XX
Product or component type	Sensor
Product name	Plant Room Air Quality Sensor
Sensor model	HS2NX
Device application	Duct Room application
Display type	LCD
Location	Living space Plant room
Mounting support	Duct Wall
Standards	EN 50081-1 EN 50082-1
Calibration certificate	Humidity: none
[Us] rated supply voltage	24 V AC 20...36 V DC
Targeted region	Europe Asia Pacific.


### Complementary

Output type	Analog 4...20 mA Analog 0...5 V DC Analog 0...10 V DC
Range compatibility	Andover Continuum sensor DMS Drayton Network 8000 Satchwell TAC I/A series TAC I/NET TAC Vista

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.7 cm
Package 1 Width	5.1 cm
Package 1 Length	10.2 cm
Package 1 Weight	1.4 g

### Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.