



Main

Net weight	0.5 kg
Product or component type	I/O module
Height	90 mm
[In] rated current	4 mA
Width	110 mm
Product certifications	CE
Ambient air temperature for storage	-20...50 °C
Depth	77 mm
Ambient air temperature for operation	0...50 °C
IP degree of protection	IP20
Power consumption in W	2 W
Relative humidity	90 % non-condensing
Number of inputs	10 digital
Range of product	TAC Xenta

Complementary

Minimum pulse duration	0.02 s
Range compatibility	TAC Xenta 401 TAC Menta TAC Xenta 300
Standards	EN 50082-1 EN 50081-1
Material	ABS + PC: enclosure
Display type	LED red LED green

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.4 cm
Package 1 Width	9.6 cm
Package 1 Length	13.0 cm
Package 1 Weight	180.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts & cables product
Contractual warranty	
Warranty	24 months