



### Main

Product or component type	Controller
Function available	Control the air flow and heating
Width	126 mm
Product certifications	LonMark[RETURN]C-Tick[RETURN]CE
Ambient air temperature for storage	-20...50 °C
IP degree of protection	IP30
Ambient air temperature for operation	0...50 °C
Relative humidity	90 % non-condensing
[Us] rated supply voltage	24 V AC -10%,+20%
Height	127 mm
Product weight	0.4 kg
Depth	50 mm
Range of product	TAC Xenta

### Complementary

System requirements	LonWorks network
Product compatibility	TAC Xenta 100 STR 100 TAC Xenta OP
Mounting support	DIN rail
Flame retardance	5VB conforming to UL 94
Standards	EN 61000-6-3 EN 61000-6-1 EN 61010-1 FCC part 15 UL 916
Material	ABS/PC: enclosure
Range compatibility	TAC Vista
Power consumption in VA	6 VA

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	12.7 cm
Package 1 Length	12.7 cm
Package 1 Weight	278.6 g

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	24 months
----------	-----------