



Main

Product or component type	Controller
Function available	Operating and application modes
Width	159 mm
Product certifications	LonMark[RETURN]C-Tick[RETURN]CE
Ambient air temperature for storage	-20...50 °C
IP degree of protection	NEMA 1 IP10
Ambient air temperature for operation	0...50 °C
Relative humidity	90 % non-condensing
[Us] rated supply voltage	24 V AC +/- 20 %
Height	197 mm
Product weight	1.04 kg
Depth	63 mm
Range of product	TAC Xenta

Complementary

System requirements	LonWorks network
Product compatibility	I/STAT M/STAT
Mounting support	Wall-mount
Flame retardance	5VB conforming to UL 94
Standards	EN 61000-6-3 EN 61000-6-1 EN 61010-1 FCC part 15 UL 916
Material	ABS/PC: enclosure
Range compatibility	STR200 STR202 STR250
Power consumption in VA	9 VA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.1 cm
Package 1 Width	15.5 cm
Package 1 Length	21.0 cm
Package 1 Weight	1.133 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	24 months
----------	-----------