



### Main

Product or component type	Valve
Valve type	Shoe
Valve product series	VTRE
Valve model	VTRE/125/280
Medium compatibility	Glycol 25 % Glycol 30 % Glycol 50 % Water
Valve configuration	3-Way
Valve connection type	Flanged
Body size	125 mm (5 in)
Pipe size	125 mm
Flow characteristic	Equal percentage
Flow coefficient	323.74 cv 280 kvs
Pressure class	PN6
Operating fluid temperature	-10...110 °C
Valve Rotation	90 °
Seat leakage	Port A: Less than 1 % of kvs
Stem movement	Rotary
Trim material	Brass
Body material	Cast iron
Material sleeve	Brass
Targeted region	Europe Asia Pacific. Australia.

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.5 cm
Package 1 Width	31.5 cm
Package 1 Length	31.0 cm
Package 1 Weight	26.25 kg

### Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.