



Main

Product or component type	Actuator
Actuator type	Electric
Actuator product series	MZ20
Actuator model	MZ20
Product destination	Zone valves
Hold-in power consumption in VA	1 VA AC
Power loss return	Non-spring return
Control signal	Proportional/modulating
Targeted region	Europe Asia Pacific. Australia.

Complementary

Actuator	Linear
Control type	Automatic reset
Rated supply voltage	24 V AC
Analogue input range	0...10 V DC
Stroke length	5.5 mm
Stroke auto calibration	False
Force N	200 N
Force lbf	45 lbf
Position indicator	Stem position cut out on yoke
Lead length	1.5 m
Connection valve	Coupling ring M30 x 1.5
Stroke running time	117 s

Environment

IP degree of protection	IP43
Ambient air temperature for operation	-5...55 °C
Relative humidity	5...95 % non-condensing
Ambient air temperature for storage	-25...65 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.0 cm
Package 1 Width	9.5 cm
Package 1 Length	12.0 cm
Package 1 Weight	259.0 g

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile