



Main

Range of product	Acti9
Product or component type	OC or fault contact
Device short name	iOF+SD 24
Signal contacts composition	1 C/O
[In] rated current	2...100 mA at 24 V, DC
9 mm pitches	1

Complementary

Local signalling	Mechanical indicator
Mounting mode	Clip-on
Mounting support	DIN rail
Height	86 mm
Width	9 mm
Depth	71 mm
Net weight	30 g
Colour	White
Connections - terminals	Spring-loaded terminal Ti241 cable(s) 0.5...1.5 mm ² - rigid Spring-loaded terminal Ti241 cable(s) 0.5...1.5 mm ² - flexible
Wire stripping length	10 mm

Environment

Standards	EN/IEC 60947-5-1 EN/IEC 60947-5-4
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	8.000 cm
Package 1 Length	9.800 cm
Package 1 Weight	47.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	72
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	4.259 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins