



Main

Range of product	Acti9
Product or component type	Cartridge
Range compatibility	Acti9 Acti9 iPRD1 surge arrester
Surge arrester type	Electrical distribution network

Complementary

Surge arrester class type	Type 1 + 2
Surge arrester technology	MOV
Product destination	Surge protection device iPRD1 12.5
Earthing system	TN-C TT TN-S
[Ue] rated operational voltage	230 V AC 50...60 Hz
Nominal discharge current	20 kA
[Uc] maximum continuous operating voltage	350 V
Maximum [Up] voltage protection level	<1.5 kV type 1 + 2
Local signalling	Mechanical indicator (white and red)
Mounting mode	Plug-in
Mounting support	Into SPD module
Height	57 mm
Width	18 mm
Depth	56 mm
Net weight	112 g
Colour	White (RAL 9003)
Material	PBT (polybutylene terephthalate)
Response time	< 25 ns

Environment

Standards	EN 61643-11 IEC 61643-11
IP degree of protection	IP20 front face:
Relative humidity	25...90 %
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...80 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.2 cm
Package 1 Width	7.7 cm
Package 1 Length	9.2 cm
Package 1 Weight	131 g
Unit Type of Package 2	BB1
Number of Units in Package 2	12
Package 2 Height	8.5 cm
Package 2 Width	10 cm
Package 2 Length	27.5 cm
Package 2 Weight	1.652 kg
Unit Type of Package 3	S02
Number of Units in Package 3	36
Package 3 Height	15 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	5.335 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins