



Main

Range	PowerTag
Product or component type	Input module
Device short name	PowerTag C 2DI 230V
Product name	PowerTag Control
Concentrator compatibility	Acti9 PowerTag Link Acti9 PowerTag Link HD
Range compatibility	Acti9 OF and SD double OC or fault contact

Complementary

[Us] rated supply voltage	230 V AC (+/- 20 %)
Network frequency	50/60 Hz
Power consumption in VA	3 VA
Digital input number	2
Input type	Dry contact 230 V AC 2 mA
Voltage state 1 guaranteed	>= 164 V for digital input
Voltage state 0 guaranteed	<= 40 V for digital input
Current state 1 guaranteed	>= 2 mA (digital input)
Current state 0 guaranteed	<= 0.5 mA (digital input)
Mounting mode	Clip-on
Mounting support	DIN rail
Local signalling	Green, orange and red LED for product status
Switching frequency	10 Hz maximum
Colour	White (RAL 9003)
9 mm pitches	2
Height	85 mm
Material	PA6 GF30
Width	18 mm
Depth	62 mm
Net weight	75 g
Connections - terminals	Tunnel type terminals (top) - 1 cable(s) 1...16 mm ² (AWG 18...AWG 16) - rigid Tunnel type terminals (top) - 1 cable(s) 0.5...10 mm ² (AWG 21...AWG 8) - flexible Tunnel type terminals (bottom) - 1 cable(s) 1...6 mm ² (AWG 18...AWG 10) - rigid Tunnel type terminals (bottom) - 1 cable(s) 0.5...4 mm ² (AWG 21...AWG 12) - flexible Tunnel type terminals (bottom) - 1 cable(s) 0.5...4 mm ² (AWG 21...AWG 12) - flexible with ferrule Tunnel type terminals (bottom) - 2 cable(s) 1.5...2.5 mm ² (AWG 16...AWG 14) - rigid Tunnel type terminals (bottom) - 2 cable(s) 1.5...2.5 mm ² (AWG 16...AWG 14) - flexible
Wire stripping length	14 Mm for top connection 9 mm for bottom connection

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Tightening torque	Power supply: 2 N.m top Digital input: 1 N.m bottom
Standards	ETSI EN 300 328 ETSI EN 301 489-1 EN/IEC 61326-1 ETSI EN 301 489-17 EN/IEC 61010-1 EN/IEC 62479 EN/IEC 61010-2-201

Environment

IP degree of protection	IP20 casing: conforming to IEC 60529 IP40 front face: conforming to IEC 60529
Pollution degree	3
Overvoltage category	III conforming to IEC 61010-1
IK degree of protection	IK05
Relative humidity	0...93 % at 40 °C conforming to IEC 60068-2-78
Operating altitude	0...2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...85 °C
Fire resistance	960 °C / 30 s conforming to UL 94 V0

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.700 cm
Package 1 Width	8.000 cm
Package 1 Length	11.500 cm
Package 1 Weight	111.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	80
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	9.137 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins