


ABWRS203L04

Empty enclosure, Prisma XS, wall-mounted, without door, IP30, (W) 550mm x (H) 500mm x (D) 210mm



Main

Range	Prisma
Product name	Prisma XS
Product or component type	Enclosure
Enclosure type	Empty enclosure
Enclosure/cubicle description	Wall-mounted enclosure depth 210 mm
Width	550 mm
Height	500 mm
Depth	210 mm
Embedding depth	210 mm
Number of 18 mm modules per row	6 x 12
Electrical insulation class	Class II
Additional information	Can be combined side by side and one on top of another
Condition of use	Indoor
Provided equipment	4 x cable entry plate
Type of front cover	Without

Complementary

Cable entry	Entry from the bottom or from the top
Enclosure mounting	Flush Surface Recessed
Mounting support	Hollow wall Concrete
9 mm pitches	144
Total number of 18 mm modules	72
[In] rated current	400 A
Enclosure material	Enclosure: powder coated steel Inside enclosure: plastic
Net weight	6.200 kg
Colour	White (RAL 9016)

Environment

IP degree of protection	IP30
IK degree of protection	IK10
Standards	IEC 61439 EN 62208

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	53 cm
Package 1 Width	56 cm
Package 1 Length	22 cm

Package 1 Weight	7.5 kg
Unit Type of Package 2	P12
Number of Units in Package 2	12
Package 2 Height	127 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Package 2 Weight	102 kg