

Product data sheet

Characteristics

ABWRS306

Empty enclosure, Prisma XS, wall-mounted, with door, IP44, (W) 800mm x (H) 950mm x (D) 210mm



Main

Range	Prisma
Product name	Prisma XS
Product or component type	Enclosure
Enclosure type	Empty enclosure
Enclosure/cubicle description	Wall-mounted enclosure depth 210 mm
Width	800 mm
Height	950 mm
Depth	210 mm
Embedding depth	210 mm
Number of 18 mm modules per row	18 x 12
Electrical insulation class	Class II
Additional information	Can be combined side by side and one on top of another
Condition of use	Indoor
Provided equipment	6 x cable entry plate 1 x double door
Type of front cover	Plain door

Complementary

Cable entry	Entry from the bottom or from the top
Door type	Internal plain
Number of locks	3
Door opening side	Reversible
Door opening angle	110 °
Enclosure mounting	Flush Surface Recessed
Mounting support	Hollow wall Concrete
9 mm pitches	432
Total number of 18 mm modules	216
[In] rated current	400 A
Locking options description	Sealable Keylock option
Enclosure material	Enclosure: powder coated steel Door: powder coated steel Inside enclosure: plastic
Net weight	19.700 kg
Colour	White (RAL 9016)

Environment

IP degree of protection	IP44
IK degree of protection	IK10
Standards	IEC 61439 DIN VDE 0603 part 1 EN 62208

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	98 cm
Package 1 Width	81 cm
Package 1 Length	22 cm
Package 1 Weight	22.549 kg
Unit Type of Package 2	P12
Number of Units in Package 2	3
Package 2 Height	96 cm
Package 2 Width	80 cm
Package 2 Length	120 cm
Package 2 Weight	79.647 kg