

Product data sheet

Characteristics

ABWRS309Z04

Distribution enclosure with 4 meter panels,
Prisma XS, wall-mounted, w/o door, IP30,
(W)800mm x (H)1400mm x (D)210mm



Main

Range	Prisma
Product name	Prisma XS
Product or component type	Enclosure
Enclosure type	Distribution enclosure with metering
Enclosure/cubicle description	Wall-mounted enclosure depth 210 mm
Width	800 mm
Height	1400 mm
Depth	210 mm
Embedding depth	210 mm
Number of 18 mm modules per row	4 x 24 2 x 12
Electrical insulation class	Class II
Additional information	Can be combined side by side and one on top of another
Condition of use	Indoor
Provided equipment	6 x cable entry plate 4 x metering plate 6 x DIN rail panel
Type of front cover	Without

Complementary

Cable entry	Entry from the bottom or from the top
Enclosure mounting	Flush Surface Recessed
Mounting support	Hollow wall Concrete
9 mm pitches	240
Total number of 18 mm modules	120
[In] rated current	63 A
Enclosure material	Enclosure: powder coated steel Inside enclosure: plastic
Net weight	32.830 kg
Colour	White (RAL 9016)

Environment

IP degree of protection	IP30
IK degree of protection	IK10
Standards	IEC 61439 EN 62208

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	143 cm
Package 1 Width	81 cm
Package 1 Length	22 cm
Package 1 Weight	34.43 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	3
Package 2 Height	96 cm
Package 2 Width	80 cm
Package 2 Length	147 cm
Package 2 Weight	118.29 kg