

ABWRS312L04

Empty enclosure, Prisma XS, floor-standing, without door, IP30, (W) 800mm x (H) 1980mm x (D) 210mm



Main

Range	Prisma
Product name	Prisma XS
Product or component type	Enclosure
Enclosure type	Empty enclosure
Enclosure/cubicle description	Floor-standing enclosure depth 210 mm
Width	800 mm
Height	1980 mm
Depth	210 mm
Embedding depth	210 mm
Number of 18 mm modules per row	36 x 12
Electrical insulation class	Class II
Additional information	Can be combined side by side and one on top of another
Condition of use	Indoor
Provided equipment	6 x cable entry plate
Type of front cover	Without

Complementary

Cable entry	Entry from the bottom or from the top
Enclosure mounting	Floor-standing
Mounting support	Hollow wall Concrete
9 mm pitches	864.0
Total number of 18 mm modules	432.0
[In] rated current	400 A
Enclosure material	Enclosure: powder coated steel
Net weight	38.200 kg
Colour	White (RAL 9016)

Environment

IP degree of protection	IP30
IK degree of protection	IK10
Standards	IEC 61439 EN 62208

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	200 cm
Package 1 Width	82 cm
Package 1 Length	23 cm
Package 1 Weight	42.2 kg
Unit Type of Package 2	PAL

Number of Units in Package 2	3
Package 2 Height	96 cm
Package 2 Width	80 cm
Package 2 Length	220 cm
Package 2 Weight	146.6 kg