ABWRS409Z18

Distribution enclosure with 8 meter panels, Prisma XS, wall-mounted, w/o door, IP30, (W)1050mm x (H)1400mm x (D)210mm



Main	
Range	Prisma
Product name	Prisma XS
Product or component type	Enclosure
Enclosure type	Distribution enclosure with metering
Enclosure/cubicle description	Wall-mounted enclosure depth 210 mm
Width	1050 mm
Height	1400 mm
Depth	210 mm
Embedding depth	210 mm
Number of 18 mm modules per row	4 x 24
Electrical insulation class	Class II
Additional information	Can be combined side by side and one on top of another
Condition of use	Indoor
Provided equipment	8 x cable entry plate 8 x metering plate 4 x DIN rail panel
Type of front cover	Without

Complementary

Cable entry	Entry from the bottom or from the top	
Enclosure mounting	Flush Surface Recessed	
Mounting support	Hollow wall Concrete	
9 mm pitches	192	
Total number of 18 mm modules	96	
[In] rated current	63 A	
Enclosure material	Enclosure: powder coated steel Inside enclosure: plastic	
Net weight	41.370 kg	
Colour	White (RAL 9016)	

Environment

IP degree of protection	IP30	
IK degree of protection	IK10	
Standards	IEC 61439 EN 62208	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	143 cm
Package 1 Width	106 cm
Package 1 Length	22 cm
Package 1 Weight	43.6 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	3
Package 2 Height	121 cm
Package 2 Width	80 cm
Package 2 Length	147 cm
Package 2 Weight	145.8 kg