BMENOP0300C

Communication module, Modicon M580, IEC 61850, coated





Main

Range of product	Modicon M580
Product or component type	Communication module

Complementary

Product compatibility	M580 PAC	
Physical interface	3 Ethernet 10/100BASE-TX	
Transmission support medium	Ethernet cable	
Transmission rate	10 Mbit/s 100 Mbit/s	
Communication service	MMS messaging client for IEC 61850 MMS messaging server for IEC 61850 Goose for IEC 61850 Modbus TCP messaging RSTP support IP forwarding	
Current consumption	1250 mA at 3.3 V DC internal	
Module format	Standard	
Net weight	0.24 kg	

Environment

Ambient air temperature for operation	00° C
Ambient air temperature for storage	-4085 °C
Relative humidity	095 % without condensation
Operating altitude	<= 2000 m
Protective treatment	Conformal coating
Directives	2014/35/EU - low voltage directive 2014/30/EU - electromagnetic compatibility 2014/34/EU - ATEX directive
Product certifications	CE[RETURN]UL[RETURN]CSA[RETURN]RCM[RETURN]EAC[RETURN]Merchant Navv[RETURN]ATEX zone 2/22[RETURN]IECEx zone 2/22

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intellability of these products for specific user applications. It is the douwn party such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Standards	EN/IEC 61131-2
	EN/IEC 61010-2-201
	UL 61010-2-201
	CSA C22.2 No 61010-2-201
	IACS E10
	EN/IEC 61000-6-5 interface type 1 and type 2
	EN/IEC 61850-3 location G
	EN/IEC 60079-0
Environmental characteristic	Gas resistant class Gx conforming to ISA S71.04
	Gas resistant class 3C4 conforming to IEC 60721-3-3
	Dust resistant class 3S4 conforming to IEC 60721-3-3
	Sand resistant class 3S4 conforming to IEC 60721-3-3
	Salt resistant level 2 conforming to IEC 68252
	Mold growth resistant class 3B2 conforming to IEC 60721-3-3
	Fungal spore resistant class 3B2 conforming to IEC 60721-3-3
	Hazardous location class I division 2

Packing Units

PCE
1
5.500 cm
11.100 cm
11.600 cm
265.000 g
S02
5
15.000 cm
30.000 cm
40.000 cm
1.659 kg

Offer Sustainability

REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
Yes
China RoHS Declaration
₫Yes
Product Environmental Profile
End Of Life Information
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins