

# Product data sheet

## Characteristics

# C103TM040

Trip unit TM40D, ComPacT NSX100/160, 3 poles, thermal magnetic protections, 40A rating



### Main

Range	ComPacT new generation
Range of product	ComPacT NSX100...250 new generation ComPacT NSX100...250 DC new generation
Product or component type	Trip unit
Trip unit name	TM-D
Trip unit technology	Thermal-magnetic
Range compatibility	ComPacT new generation NSX100 ComPacT new generation NSX160 ComPacT new generation NSX100 DC
Device application	Distribution
Poles description	3P
Protected poles description	3D
Trip unit protection functions	LI
Protection type	L : for overload protection (thermal) I : for short-circuit protection (magnetic)
Trip unit rating	40 A at 40 °C
[Ue] rated operational voltage	690 V AC 50/60 Hz 750 V DC
Network type	AC DC
Network frequency	50/60 Hz
Circuit breaker mounting mode	Fixed

### Complementary

Long-time pick-up adjustment type $I_r$ (thermal protection)	Adjustable
[ $I_r$ ] long-time protection pick-up adjustment range	0.7...1 x $I_n$
Long-time protection delay adjustment type $t_r$	Fixed
[ $t_r$ ] long-time protection delay adjustment range	120...400 S at 1.5 x $I_n$ 15 s at 6 x $I_r$
Instantaneous protection pick-up adjustment type $I_i$	Fixed
[ $I_i$ ] instantaneous protection pick-up adjustment range	500 A
Earth-leakage protection	Without

### Environment

Standards	EN/IEC 60947-2
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60947-1
IP degree of protection	IP40 conforming to IEC 60529
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	10.0 cm
Package 1 Length	11.5 cm
Package 1 Weight	424.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	28
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	12.154 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	 <a href="#">End Of Life Information</a>