

C104100D1S

Switch disconnecter ComPacT NSX100NA DC
PV. 100A rating. 4 poles



Main

Range	ComPacT new generation
Product name	ComPacT NSX DC PV
Device short name	NSX100NA DC PV
Product or component type	Switch disconnecter
Device application	Photovoltaic
Poles description	4P
[I _{th}] conventional free air thermal current	100 A at 65 °C
[I _e] rated operational current	DC-22A: 100 A DC 1000 V
[U _e] rated operational voltage	1000 V DC
Network type	DC
Suitability for isolation	Yes conforming to EN/IEC 60947-3
Utilisation category	DC-22A
Breaking capacity code	NA
Contact position indicator	Yes
Visible break	No
Mounting mode	Fixed
[I _{cw}] rated short-time withstand current	2.5 kA during 1 s
[I _{cm}] rated short-circuit making capacity	2.5 kA switch-disconnector alone
Control type	Toggle
[U _i] rated insulation voltage	1000 V DC
[U _{imp}] rated impulse withstand voltage	8 kV

Complementary

Mounting support	Backplate
Upside connection	Front
Downside connection	Front
Connection pitch	35 mm
Mechanical durability	10000 cycles
Electrical durability	1500 cycles 1000 V DC In
Width (W)	140 mm
Height (H)	161 mm
Depth (D)	86 mm
Net weight	2.8 kg
Standards	EN/IEC 60947-1 EN/IEC 60947-3
Product certifications	CE[RETURN]EAC[RETURN]CCC

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 62262
Electrical shock protection class	Class II
Pollution degree	3 conforming to IEC 60664-1
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.0 cm
Package 1 Width	14.0 cm
Package 1 Length	16.0 cm
Package 1 Weight	3.0 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes