

# C104TM063

Trip unit TM63D, ComPacT NSX100/160/250, 4 poles 4D (neutral fully protected), thermal magnetic protections, 63A rating



## Main

|                                |   |
|--------------------------------|---|
| Range                          | ComPacT new generation  |
| Range of product               | ComPacT NSX100...250 new generation<br>ComPacT NSX100...250 DC new generation   |
| Product or component type      | Trip unit   |
| Trip unit name                 | TM-D  |
| Trip unit technology           | Thermal-magnetic  |
| Range compatibility            | ComPacT new generation NSX100<br>ComPacT new generation NSX160<br>ComPacT new generation NSX250<br>ComPacT new generation NSX100 DC |
| Device application             | Distribution  |
| Poles description              | 4P  |
| Protected poles description    | 4D  |
| Neutral position               | Left  |
| Trip unit protection functions | LI  |
| Protection type                | L : for overload protection (thermal)<br>I : for short-circuit protection (magnetic)  |
| Trip unit rating               | 63 A at 40 °C   |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz<br>750 V DC   |
| Network type                   | AC<br>DC  |
| Network frequency              | 50/60 Hz  |
| Circuit breaker mounting mode  | Fixed   |

## Complementary

|   |   |
|---|---|
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable                                |
| [Ir] long-time protection pick-up adjustment range        | 0.7...1 x In                              |
| Long-time protection delay adjustment type tr             | Fixed                                     |
| [tr] long-time protection delay adjustment range          | 120...400 S at 1.5 x In<br>15 s at 6 x Ir |
| Neutral protection settings                               | 1 x Ir (4D)                               |
| Instantaneous protection pick-up adjustment type li       | Fixed                                     |
| [li] instantaneous protection pick-up adjustment range    | 500 A                                     |
| Earth-leakage protection                                  | Without                                   |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Standards                             | EN/IEC 60947-2               |
| Electrical shock protection class     | Class II                     |
| Pollution degree                      | 3 conforming to IEC 60947-1  |
| IP degree of protection               | IP40 conforming to IEC 60529 |
| Ambient air temperature for operation | -25...70 °C                  |
| Ambient air temperature for storage   | -50...85 °C                  |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 6.7 cm    |
| Package 1 Width              | 9.8 cm    |
| Package 1 Length             | 14.8 cm   |
| Package 1 Weight             | 494.0 g   |
| Unit Type of Package 2       | S03       |
| Number of Units in Package 2 | 23        |
| Package 2 Height             | 30.0 cm   |
| Package 2 Width              | 30.0 cm   |
| Package 2 Length             | 40.0 cm   |
| Package 2 Weight             | 11.752 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant with Exemptions                     |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | <a href="#">End Of Life Information</a>       |