C104TM080

Trip unit TM80D, ComPacT NSX100/160/250, 4 poles 4D (neutral fully protected), thermal magnetic protections, 80A rating





Main

| Range | ComPacT new generation |
|--------------------------------|---|
| Range of product | ComPacT NSX100250 new generation |
| Product or component type | Trip unit |
| Trip unit name | TM-D |
| Trip unit technology | Thermal-magnetic |
| Range compatibility | ComPacT new generation NSX100 ComPacT new generation NSX160 ComPacT new generation NSX250 |
| Device application | Distribution |
| Poles description | 4P |
| Protected poles description | 4D |
| Neutral position | Left |
| Trip unit protection functions | LI |
| Protection type | L : for overload protection (thermal) I : for short-circuit protection (magnetic) |
| Trip unit rating | 80 A at 40 °C |
| [Ue] rated operational voltage | 690 V AC 50/60 Hz |
| Network type | AC |
| Network frequency | 50/60 Hz |
| Circuit breaker mounting mode | Fixed |
| | |

Complementary

| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable |
|---|--|
| [Ir] long-time protection pick-up adjustment range | 0.71 x ln |
| Long-time protection delay adjustment type tr | Fixed |
| [tr] long-time protection delay adjustment range | 120400 S at 1.5 x ln 15 s at 6 x lr |
| Neutral protection settings | 1 x lr (4D) |
| Instantaneous protection pick-up adjustment type li | Fixed |
| [li] instantaneous protection pick-up adjustment range | 640 A |
| Earth-leakage protection | Without |

Environment

| Standards | EN/IEC 60947-2 | |
|---------------------------------------|------------------------------|--|
| Electrical shock protection class | Class II | |
| Pollution degree | 3 conforming to IEC 60947-1 | |
| IP degree of protection | IP40 conforming to IEC 60529 | |
| Ambient air temperature for operation | -2570 °C | |
| Ambient air temperature for storage | -5085 °C | |

Packing Units

| 3 | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.7 cm |
| Package 1 Width | 9.8 cm |
| Package 1 Length | 14.8 cm |
| Package 1 Weight | 498.0 g |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 23 |
| Package 2 Height | 30.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 11.858 kg |
| | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------|-------------------------------|--|
| REACh Regulation | ☑ REACh Declaration | |
| EU RoHS Directive | Compliant with Exemptions | |
| Mercury free | Yes | |
| China RoHS Regulation | ☐ China RoHS Declaration | |
| RoHS exemption information | ₽¥Yes | |
| Environmental Disclosure | Product Environmental Profile | |
| Circularity Profile | End Of Life Information | |