

# C11E4TM080B

Circuit breaker, ComPacT NSXm 160E, 16kA/415VAC, 4 poles 4D (neutral fully protected), TMD trip unit 80A, lugs/busbars



## Main

|  |   |
|--|---|
| Range  | ComPacT new generation  |
| Product name   | ComPacT NSXm new generation   |
| Range of product                                     | ComPacT NSXm new generation   |
| Device short name                                    | NSXm 160E   |
| Product or component type                            | Circuit breaker   |
| Device application                                   | Distribution  |
| Poles description                                    | 4P  |
| Protected poles description                          | 4D  |
| Neutral position                                     | Left  |
| [In] rated current                                   | 80 A at 40 °C   |
| [Ue] rated operational voltage                       | 690 V AC 50/60 Hz   |
| Network type   | AC  |
| Network frequency                                    | 50/60 Hz  |
| Suitability for isolation                            | Yes conforming to IEC 60947-2   |
| Utilisation category                                 | Category A  |
| [Icu] rated ultimate short-circuit breaking capacity | 25 KA Icu at 220...240 V AC 50/60 Hz conforming to IEC 60947-2<br>16 KA Icu at 380...415 V AC 50/60 Hz conforming to IEC 60947-2<br>10 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>8 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | E 16 kA 415 V AC  |
| Trip unit name                                       | TM-D  |
| Trip unit technology                                 | Thermal-magnetic  |
| Trip unit protection functions                       | LI  |
| Control type   | Toggle  |
| Circuit breaker mounting mode                        | Fixed   |

## Complementary

|   |   |
|---|---|
| [Ui] rated insulation voltage                       | 800 V AC 50/60 Hz   |
| [Uimp] rated impulse withstand voltage              | 8 kV  |
| [Ics] rated service short-circuit breaking capacity | 25 KA at 220...240 V AC 50/60 Hz conforming to IEC 60947-2<br>16 KA at 380...415 V AC 50/60 Hz conforming to IEC 60947-2<br>10 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>8 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 20000 cycles  |
| Electrical durability                               | 20000 Cycles at 440 V In/2<br>10000 Cycles at 440 V In<br>10000 Cycles at 690 V In/2<br>5000 cycles at 690 V In   |
| Power dissipation per pole                          | 6.96 W  |
| Mounting support                                    | Backplate   |

|   |  |
|---|--|
| Mounting position   | Horizontal and vertical<br>Flat on the back  |
| Upside connection   | Front  |
| Downside connection                                       | Front  |
| Connection terminals                                      | Compression lug/busbar   |
| Connection pitch  | 35 Mm with spreaders<br>27 mm without spreaders  |
| 9 mm pitches  | 12 module  |
| Trip unit rating  | 80 A at 40 °C  |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable   |
| [Ir] long-time protection pick-up adjustment range        | 0.7...1 x In   |
| Long-time protection delay adjustment type tr             | Fixed  |
| Neutral protection settings                               | 1 x Ir (4D)  |
| Instantaneous protection pick-up adjustment type li       | Fixed  |
| [li] instantaneous protection pick-up adjustment range    | 1000 A   |
| Earth-leakage protection                                  | Without  |
| Number of slots for electrical auxiliaries                | 1 slot(s) for auxiliary switch OF<br>1 slot(s) for alarm switch SD<br>1 slot(s) for voltage release MN or MX |
| Local signalling  | Flag (green) for presence of auxiliary contacts  |
| Width (W)   | 108 mm   |
| Height (H)  | 137 mm   |
| Depth (D)   | 80 mm  |
| Net weight  | 1.42 kg  |
| Colour  | Grey (RAL 7016)  |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | EN/IEC 60947                                    |
| Pollution degree                      | 3 conforming to IEC 60664-1                     |
| IP degree of protection               | IP40 conforming to IEC 60529                    |
| IK degree of protection               | IK07 conforming to IEC 62262                    |
| Ambient air temperature for operation | -25...70 °C                                     |
| Ambient air temperature for storage   | -50...85 °C                                     |
| Relative humidity                     | 0...95 %  |
| Operating altitude                    | 2000 m without derating<br>5000 m with derating |

## Packing Units

|                              |            |
|------------------------------|------------|
| Unit Type of Package 1       | PCE        |
| Number of Units in Package 1 | 1          |
| Package 1 Height             | 12.000 cm  |
| Package 1 Width              | 13.000 cm  |
| Package 1 Length             | 22.000 cm  |
| Package 1 Weight             | 1.166 kg   |
| Unit Type of Package 2       | P12        |
| Number of Units in Package 2 | 144        |
| Package 2 Height             | 150.000 cm |
| Package 2 Width              | 80.000 cm  |
| Package 2 Length             | 120.000 cm |
| Package 2 Weight             | 254.490 kg |

## Offer Sustainability

|                             |   |
|-----------------------------|---|
| Sustainable offer status    | Green Premium product                         |
| REACH Regulation            | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive           | Compliant with Exemptions                     |
| Mercury free                | Yes   |
| China RoHS Regulation       | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information  | <a href="#">Yes</a>                           |
| Environmental Disclosure    | <a href="#">Product Environmental Profile</a> |
| Circularity Profile         | No need of specific recycling operations      |
| Halogen content performance | Halogen free plastic parts product            |