

Product data sheet

Characteristics

C125S3FM

Switch disconnector basic frame, ComPacT
NS1250 type NA, 3P, fixed, manually operated,
1250A



Main

Product name	ComPacT NS new generation
Product or component type	Basic frame
Device application	Distribution
Poles description	3P
Network type	AC
Breaking capacity code	NA
Suitability for isolation	Yes conforming to IEC 60947-3

Complementary

Network frequency	50/60 Hz
Control type	Manually operated
Mounting mode	Fixed
Upside connection	Front
Downside connection	Front
[Ie] rated operational current	AC-23A: 1250 A AC 50/60 Hz 220/240 V AC-23A: 1250 A AC 50/60 Hz 380/415 V AC-23A: 1250 A AC 50/60 Hz 440/480 V AC-23A: 1250 A AC 50/60 Hz 500/525 V AC-23A: 1250 A AC 50/60 Hz 660/690 V
[Ui] rated insulation voltage	800 V AC 50/60 Hz conforming to IEC 60947-3
[Uimp] rated impulse withstand voltage	8 kV conforming to IEC 60947-3
[Ith] conventional free air thermal current	1250 A at 60 °C
[Icw] rated short-time withstand current	25 KA during 0.5 s conforming to IEC 60947-3 4 kA during 20 s conforming to IEC 60947-3
[Icm] rated short-circuit making capacity	52 kA 690 V AC at 50/60 Hz
[Ue] rated operational voltage	690 V AC 50/60 Hz conforming to IEC 60947-3
Contact position indicator	Yes
Visible break	No
Mechanical durability	10000 cycles conforming to IEC 60947-3
Electrical durability	2000 cycles 440 V AC 50/60 Hz conforming to IEC 60947-3
Connection pitch	70 mm
Height	210 mm
Width	327 mm
Depth	147 mm
Net weight	14 kg

Environment

Standards	IEC 60947-3
Product certifications	IEC66 CB Scheme
IP degree of protection	IP40 conforming to IEC 60529
IK degree of protection	IK07 conforming to EN 50102
Pollution degree	3 conforming to IEC 60947-3

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-50...85 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0 cm
Package 1 Width	1.0 cm
Package 1 Length	2.0 cm
Package 1 Weight	10.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	 End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins