

# C25H32D100

Circuit breaker, ComPacT NSX250H,  
70kA/415VAC, 3 poles, MicroLogic 2.2 trip unit  
100A



## Main

|                                                      |                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                                | ComPacT new generation                                                                                                                                                                                                                                                                                                                                                                                                               |
| Product name                                         | ComPacT NSX new generation                                                                                                                                                                                                                                                                                                                                                                                                           |
| Device short name                                    | NSX250H                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Product or component type                            | Circuit breaker                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Device application                                   | Distribution                                                                                                                                                                                                                                                                                                                                                                                                                         |
| Poles description                                    | 3P                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Protected poles description                          | 3D                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| [In] rated current                                   | 100 A at 40 °C                                                                                                                                                                                                                                                                                                                                                                                                                       |
| [Ue] rated operational voltage                       | 690 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Network type                                         | AC                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Network frequency                                    | 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                                                                                     |
| Utilisation category                                 | Category A                                                                                                                                                                                                                                                                                                                                                                                                                           |
| [Icu] rated ultimate short-circuit breaking capacity | 100 KA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>70 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>65 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>50 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>35 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 KA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2<br>15 kA at 600 V AC 50/60 Hz conforming to UL 508 |
| Performance level                                    | H 70 kA 415 V AC                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Trip unit name                                       | MicroLogic 2.2                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Trip unit technology                                 | Electronic                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Trip unit protection functions                       | LSol                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Control type                                         | Toggle                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Circuit breaker mounting mode                        | Fixed                                                                                                                                                                                                                                                                                                                                                                                                                                |

## Complementary

|                                                     |                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ui] rated insulation voltage                       | 800 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                         |
| [Uimp] rated impulse withstand voltage              | 8 kV                                                                                                                                                                                                                                                                                                                                                      |
| [Ics] rated service short-circuit breaking capacity | 100 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>70 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>65 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>50 KA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>35 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 KA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 20000 cycles                                                                                                                                                                                                                                                                                                                                              |
| Electrical durability                               | 20000 Cycles at 440 V In/2<br>10000 Cycles at 440 V In<br>10000 Cycles at 690 V In/2<br>5000 cycles at 690 V In                                                                                                                                                                                                                                           |

|                                                           |                                                                                                                                                            |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power dissipation per pole                                | 2.7 W                                                                                                                                                      |
| Mounting support                                          | Backplate                                                                                                                                                  |
| Mounting position                                         | Horizontal and vertical<br>Flat on the back                                                                                                                |
| Upside connection                                         | Front                                                                                                                                                      |
| Downside connection                                       | Front                                                                                                                                                      |
| Connection pitch                                          | 35 mm                                                                                                                                                      |
| Protection type                                           | L : for overload protection (long time)<br>So : for short time short-circuit protection with fixed delay<br>I : for instantaneous short-circuit protection |
| Trip unit rating                                          | 100 A at 40 °C                                                                                                                                             |
| Long-time pick-up adjustment type Ir (thermal protection) | Adjustable 9 settings                                                                                                                                      |
| [Ir] long-time protection pick-up adjustment range        | 40...100 A                                                                                                                                                 |
| Long-time protection delay adjustment type tr             | Fixed                                                                                                                                                      |
| [tr] long-time protection delay adjustment range          | 400 S at 1.5 x Ir<br>16 S at 6 x Ir<br>11 s at 7.2 x Ir                                                                                                    |
| Thermal memory                                            | 20 minutes before and after tripping                                                                                                                       |
| Short-time protection pick-up adjustment type lsd         | Adjustable 9 settings                                                                                                                                      |
| [lsd] Short-time protection pick-up adjustment range      | 1.5...10 x Ir                                                                                                                                              |
| Short-time protection delay adjustment type tsd           | Fixed                                                                                                                                                      |
| Instantaneous protection pick-up adjustment type li       | Fixed                                                                                                                                                      |
| [li] instantaneous protection pick-up adjustment range    | 1500 A                                                                                                                                                     |
| Earth-leakage protection                                  | Without                                                                                                                                                    |
| Zone selective interlocking ZSI                           | Without                                                                                                                                                    |
| Number of slots for electrical auxiliaries                | 5 slot(s)                                                                                                                                                  |
| Local signalling                                          | Flashing LED (green) for ready to operate<br>LED 105 % Ir (red) for overload<br>LED 90 % Ir (orange) for overload                                          |
| Width (W)                                                 | 105 mm                                                                                                                                                     |
| Height (H)                                                | 161 mm                                                                                                                                                     |
| Depth (D)                                                 | 86 mm                                                                                                                                                      |
| Net weight                                                | 2.4 kg                                                                                                                                                     |

## Environment

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Standards                             | EN/IEC 60947                                                 |
| Product certifications                | Marine[RETURN]CCC[RETURN]EAC                                 |
| Overvoltage category                  | Class II                                                     |
| Electrical shock protection class     | Class II                                                     |
| Pollution degree                      | 3 conforming to IEC 60664-1                                  |
| IP degree of protection               | IP40 conforming to IEC 60529                                 |
| IK degree of protection               | IK07 conforming to IEC 62262                                 |
| Ambient air temperature for operation | -25...70 °C                                                  |
| Ambient air temperature for storage   | -50...85 °C                                                  |
| Relative humidity                     | 0...95 %                                                     |
| Operating altitude                    | 0...2000 m without derating<br>2000 m...5000 m with derating |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 12 cm    |
| Package 1 Width              | 14 cm    |
| Package 1 Length             | 20 cm    |
| Package 1 Weight             | 2.048 kg |
| Unit Type of Package 2       | S03      |

|                              |          |
|------------------------------|----------|
| Number of Units in Package 2 | 4        |
| Package 2 Height             | 30 cm    |
| Package 2 Width              | 30 cm    |
| Package 2 Length             | 40 cm    |
| Package 2 Weight             | 8.192 kg |
| Unit Type of Package 3       | P12      |
| Number of Units in Package 3 | 72       |
| Package 3 Height             | 150 cm   |
| Package 3 Width              | 80 cm    |
| Package 3 Length             | 120 cm   |
| Package 3 Weight             | 147.7 kg |

## Offer Sustainability

|                            |                                               |
|----------------------------|-----------------------------------------------|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant with Exemptions                     |
| Mercury free               | Yes                                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | <a href="#">End Of Life Information</a>       |