

# C25H34V250

Circuit breaker ComPacT NSX250H, 70kA at 415VAC, MicroLogic 4.2 Vigi trip unit 250A, 3 poles 3d



## Main

|  |   |
|--|---|
| Range  | ComPacT new generation  |
| Product name   | ComPacT NSX new generation  |
| Device short name                                    | NSX250H   |
| Product or component type                            | Earth leakage circuit breaker   |
| Device application                                   | Distribution  |
| Poles description                                    | 3P  |
| Protected poles description                          | 3D  |
| [In] rated current                                   | 250 A at 40 °C  |
| [Ue] rated operational voltage                       | 440 V AC 50/60 Hz   |
| Network type   | AC  |
| Network frequency                                    | 50/60 Hz  |
| Suitability for isolation                            | Yes conforming to EN/IEC 60947-2  |
| Utilisation category                                 | Category A  |
| [Icu] rated ultimate short-circuit breaking capacity | 100 KA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>70 KA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>65 KA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>50 KA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>35 KA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance level                                    | H 70 kA 415 V AC  |
| Trip unit name                                       | MicroLogic 4.2  |
| Trip unit technology                                 | Electronic  |
| Trip unit protection functions                       | LSolR   |
| Control type   | Toggle  |
| Circuit breaker mounting mode                        | Fixed   |

## Complementary

|   |   |
|---|---|
| [Ui] rated insulation voltage                       | 500 V AC 50/60 Hz   |
| [Uimp] rated impulse withstand voltage              | 8 kV  |
| [Ics] rated service short-circuit breaking capacity | 100 KA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2<br>70 KA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2<br>65 KA at 440 V AC 50/60 Hz conforming to IEC 60947-2<br>50 KA at 500 V AC 50/60 Hz conforming to IEC 60947-2<br>35 KA at 525 V AC 50/60 Hz conforming to IEC 60947-2<br>10 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical durability                               | 20000 cycles  |
| Electrical durability                               | 20000 Cycles at 440 V In/2<br>10000 Cycles at 440 V In<br>10000 Cycles at 690 V In/2<br>5000 cycles at 690 V In   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|   |  |
|---|--|
| Power dissipation per pole                                  | 25 W N<br>25 W L1 and L3<br>20.63 W L2   |
| Mounting support  | Backplate  |
| Mounting position   | Horizontal and vertical<br>Flat on the back  |
| Upside connection   | Front  |
| Downside connection   | Front  |
| Connection pitch  | 35 mm  |
| Protection type   | L : for overload protection (long time)<br>So : for short time short-circuit protection with fixed delay<br>I : for instantaneous short-circuit protection<br>R : for earth-leakage protection |
| Trip unit rating  | 250 A at 40 °C   |
| Long-time pick-up adjustment type Ir (thermal protection)   | Adjustable 9 settings  |
| [Ir] long-time protection pick-up adjustment range          | 100...250 A  |
| Long-time protection delay adjustment type tr               | Fixed  |
| [tr] long-time protection delay adjustment range            | 400 S at 1.5 x Ir<br>16 S at 6 x Ir<br>11 s at 7.2 x Ir  |
| Thermal memory  | 20 minutes before and after tripping   |
| Short-time protection pick-up adjustment type Isd           | Adjustable   |
| [Isd] Short-time protection pick-up adjustment range        | 1.5...10 x Ir  |
| Short-time protection delay adjustment type tsd             | Fixed  |
| Instantaneous protection pick-up adjustment type Ii         | Fixed  |
| [Ii] instantaneous protection pick-up adjustment range      | 3000 A   |
| Earth-leakage protection                                    | Integrated   |
| Earth-leakage protection class                              | Class A  |
| Earth-leakage protection sensitivity adjustment type IΔn    | Adjustable   |
| [IΔn] earth-leakage protection sensitivity adjustment range | 30 MA<br>100 MA<br>300 MA<br>500 MA<br>1 A<br>3 A<br>5 A   |
| Earth-leakage protection specific mode                      | OFF using the IΔn rotary switch  |
| Earth-leakage protection time delay adjustment type Δt      | Adjustable   |
| [Δt] Earth-leakage protection time delay adjustment range   | 0 Ms<br>60 Ms<br>150 Ms<br>500 Ms<br>1 s   |
| Zone selective interlocking ZSI                             | Without  |
| Number of slots for electrical auxiliaries                  | 5 slot(s)  |
| Local signalling  | Flashing LED (green) for ready to operate<br>LED 105 % Ir (red) for overload<br>LED 90 % Ir (orange) for overload  |
| Width (W)   | 105 mm   |
| Height (H)  | 161 mm   |
| Depth (D)   | 86 mm  |
| Net weight  | 2.4 kg   |

## Environment

|                                   |                              |
|-----------------------------------|------------------------------|
| Standards                         | EN/IEC 60947                 |
| Product certifications            | CCC[RETURN]EAC[RETURN]Marine |
| Overvoltage category              | Class II                     |
| Electrical shock protection class | Class II                     |
| Pollution degree                  | 3 conforming to IEC 60664-1  |

|                                       |  |
|---------------------------------------|--|
| IP degree of protection               | IP40 conforming to IEC 60529                                 |
| IK degree of protection               | IK07 conforming to IEC 62262                                 |
| Ambient air temperature for operation | -25...70 °C  |
| Ambient air temperature for storage   | -50...85 °C  |
| Relative humidity                     | 0...95 %   |
| Operating altitude                    | 0...2000 m without derating<br>2000 m...5000 m with derating |

### Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 14.0 cm   |
| Package 1 Width              | 14.0 cm   |
| Package 1 Length             | 19.0 cm   |
| Package 1 Weight             | 2.087 kg  |
| Unit Type of Package 2       | S03       |
| Number of Units in Package 2 | 6         |
| Package 2 Height             | 30.0 cm   |
| Package 2 Width              | 30.0 cm   |
| Package 2 Length             | 40.0 cm   |
| Package 2 Weight             | 12.522 kg |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product                         |
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| EU RoHS Directive          | Compliant with Exemptions                     |
| Mercury free               | Yes   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |
| RoHS exemption information | <a href="#">Yes</a>                           |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a> |
| Circularity Profile        | <a href="#">End Of Life Information</a>       |